



THE SPECIALISTS FOR
THERMOPLASTICS & ELASTOMERS

BADATRON PPS – COMPOUNDS BASED ON POLYPHENYLENE SULFIDE



- High heat distortion temperatures > 250°C
- Melting temperature approx. 295°C
- Maximum dimension stability, almost no hygroscopicity
- Excellent chemical resistance
- Filler contents available up to approx. 50 %
- Maximum rigidity and strength
- Inherent flame resistance (UL94-V0 @ 1.5 mm)



WHEN RESISTANCE MATTERS – BADATRON PPS

With Badatron PPS, its high-performance compounds, Bada AG provides its customers with material solutions for parts exposed to extreme thermal conditions and aggressive substances.

Glass-fibre reinforced Badatron compounds shows dimensional stability under heat beyond 250°C. These compounds (as opposed to polyamides) are extremely resistant to acids and bases due to their specific chemical structure. Another advantage of Badatron PPS is its negligible hygroscopicity and its excellent dimensional stability, making it the ideal material for the production of precision parts. For tribologically stressed parts, Bada AG offers PPS compounds with PTFE modification. Additional glass fibre reinforcement provides for high rigidity.

Specific solutions are our standard – please do not hesitate to contact our Application Technology Department for individual requirements. Together with you, we will develop the product solution you require.





THE SPECIALISTS FOR
THERMOPLASTICS & ELASTOMERS

BADATRON PPS – COMPOUNDS BASED ON POLYPHENYLENE SULFIDE

EXAMPLES OF USE FOR BADATRON PPS:

Badatron	PPS GF40	PPS GF40 TF5
Modification	Glass fibre	Glass fibre + PTFE
Deflection temperature (1.8 MPa)	> 250°C	> 250°C
Resistance to acids and bases	Very good	Very good
Hygroscopicity	< 0.1%	< 0.1%
Flammability	V-0 @ 1.5 mm	V-0 @ 1.5 mm
Examples of use	Pump casings, water meter, vehicle parts	Plain bearings, rotors, blades, impellers

These two types only represent a small selection of our Badatron portfolio.

The following modifications are available on request:

- Glass fibre, glass bead or mineral filling
- Carbon fibre modification for maximum strength
- Impact modification
- Types for contact with food or drinking water

Customized modifications are available on request.
Please contact our Application Technology Department!



BADAMID®

PA6, PA6.6, PA6.6/6

BADAMID®

PA6/6T, PPA, PA4.6, PA10T

BADAMID®

PA12, PA1212, PA612, PA610

BADATECH HT®

HIGH-PERFORMANCE COMPOUNDS

BADATRON®

PPS

BADAFLEX®

TPE-S (SBS, SEBS)

BADAFLEX®

TPE-E, TPU

BADAPRENE®

TPV (EPDM/PP)

BADADUR®

PBT, BLENDS

BADALAC®

ABS-SPECIALTIES, BLENDS

BADAFORM®

POM

BADALON®

PC-SPECIALTIES, BLENDS

BADAPROP®

PP-SPECIALTIES, BLENDS



Bada AG Deutschland
77815 Bühl/Baden
Tel. +49 (0)72 23-940 77-0
Fax +49 (0)72 23-940 77-77
E-Mail: info@bada.de

Bada Hispanoplast S.A. España
22006 Huesca
Tel. +34 974-23 97 74
Fax +34 974-24 39 69
E-Mail: info@bada.com.es

www.bada.de